

INDICATORS, SWITCHES DETECTORS, MONITORS



Air Line Alarm, 091-248-X

The 091-248, Air Line Alarm, alerts the driver with an audible alarm and red LED indicator if the Air Line is connected while the vehicle is running. Once the Air Line is disconnected, the alarm and LED light will turn off.

Features:

- Input: 10-16 Vdc, .030 Amps Max
- Output: 85 dB alarm
- Indicator: Device Powered: Red LED
- Cut-Out-Size:
SVR - 1.45" x .83"
NGR & Euro - 1.73" x 0.87"
- Weight: .25 lbs
- Warranty: 3 Years



Auto Touch, 091-222

Touch-On / Touch-Off switch. Built-in LED illuminates when switch is on, Lexan front panel allows for years of durability. Reverse polarity protected.

Features:

- Input Voltage: 8-20 Vdc
- Quiescent Current: 0.020 Amps Max
- Switch Rating: 5.0 Amps Max
- Cut-Out-Size: 1.45" x .83"
- Weight: .25 lbs
- Warranty: 3 Years



Bluetooth Module, 091-226

The Bluetooth Module 091-226 provides a fully integrated solution for delivering high-quality stereo audio in a small form factor. Seamlessly stream music from any Bluetooth capable device.

Features:

- Input Voltage: 11-30 vDC
- Input Current: 0.25 aDC
- Cutout Size: 1.45" x 0.83"
- Bluetooth Specification: Bluetooth v4.1
- Supported Audio Codecs: SBC, MP3, AAC, and Faststream
- Operating Distance: 10 meters Class II
- Bluetooth Module Audio Connector: 3.5mm, 4 position, female
- Audio Splitter Length: 8.5"
- Audio Cable Length: 6' 6"
- Weight: 0.5 lbs




TO PLACE AN ORDER:

Visit: www.evpeurope.com

Call: +44 (0) 1926 419441

E-mail: sales@evpeurope.com



EVP LTD
emergency vehicle products

Mini Single Bar Graph Display, 091-234

The Mini Single Bar Graph Display 091-234 is a universal display containing a 10-LED bar graph to indicate the vehicle's battery status. The top or bottom LED's blink to indicate HIGH VOLTAGE or LOW VOLTAGE is detected, respectively.

Features:

- Input Voltage: 12 to 30 VDC
- Input Current: 30mA, Max
- Temperature Range: -40F to 120F
- Cutout Size: 1.45" x 0.83"
- Bar Graph Range: 12-13 +/- 2% (bottom to top)
- Low Voltage: < 12.0 VDC (bottom LED flashes)
- High Voltage: > 14.8 VDC (top LED flashes)
- Warranty: 3 years



Shore Power Alarm, 091-231-X

The 091-231, Shore Power Alarm, alerts the driver with an audible alarm and red LED indicator if shore power is connected while the vehicle is running. Once shore power is disconnected, the alarm and LED light will turn off.

Features:

- Input: 10-16 Vdc, .030 Amps Max
- Output: 85 dB alarm
- Indicator: Device Powered: Red LED
- Cut-Out-Size:
SVR - 1.45" x 0.83"
NGR & Euro - 1.73" x 0.87"
- Weight: .25 lbs
- Warranty: 3 Years



Temperature Monitor, 091-224

The 091-224 Temperature Monitor may be used to indicate either inside or outside temperature and is designed to fit into a standard 1.45" x 0.83" panel cutout.

Features:

- Input: 11-16 Vdc, 0.25 Amps
- Remote Sensor: 16' Cable
- Temperature Range: -50°F to +150°F
- Accuracy: ±1.5°F at 72°F, ±5°F at -50°F to +150°F
- Cut-Out-Size: 1.45" x .83"
- Weight: .25 lbs
- Warranty: 3 Years



AUX/USB Pass-Through, 091-249

Relocate an Auxiliary and/or USB port to an other location with this retrofitable switch.

Features:

- Connections: Front - USB Type A Receptacle (4-pin) and 3.5mm Stereo Jack (3 conductor)
- Back - 6' USB and 6' Auxiliary Cable
- Cut-Out-Size: 1.45" x .83"
- Weight: .25 lbs
- Warranty: 3 Years



Mini Battery Voltage Display, 091-250

The Mini Battery Display is a universal indicator that displays the vehicles battery voltage. The indicator displays a 3-digit numerical value of the vehicles battery voltage. The display is accurate to 100-millivolts and has a current draw of only 40-milliamps.

Features:

- Input 10 to 15 VDC
- Input Current: 40mA, Max
- Temperature Range: -40°F to +120°F
- Voltage Meter: ±1%
- Cut-Out-Size: 1.45" x .83"
- Weight: .25 lbs
- Warranty: 3 Years



Switch Clock, 091-257

The 091-257 is a universal switch mount accessory that displays a real-time clock on an OLED panel. The Switch Clock displays a 12-hour numerical value of a clock. The clock is accurate to 1-sec per/day and has a current draw of only 6.5-milliamps.

Features:

- Input: 10 to 30 VDC
- Input Current: 6.5mA with active display (IGN input off) 0.6mA in sleep mode
- Time Keeping: +/- 1 second/day
- Temperature Range: 4° F to 140° F (-20° C to 60° C)
- Cut-Out-Size: 1.45" x .83"
- Weight: .25 lbs
- Warranty: 3 Years



Switch Enclosure, 091-255

The Switch Enclosure 091-255 is a heavy duty enclosure with two cut-outs designed to fit two standard SVR switches. Mount with two #8 screws below or on top of dashboard.

Features:

- Fits: Standard SVR switches
- Available in red, white and black
- Dimensions: 3.73 L x 2.06 W x 2.19 H
- Warranty: 3 years



Dashboard Mount Accessory, 091-239

The Dash Mount Accessory is a product made for Kussmaul dash-mountable switch accessories without the need to modify the dashboard. This box can be mounted easily above the dashboard, underneath the dashboard, or from the vehicle roof making the Kussmaul Dash Mount an easy choice to add space for retrofittable vehicle accessories in your emergency or utility vehicle.

Features:

- Accepts five (5) Kussmaul Dash Mounted Accessories 1.4" x 0.8"
- Heyco PG9 Strain Relief on rear panel for wires
- Enclosure: Painted Aluminum
- Dimensions: L3.1 in, W7.5 in, H5.5 in
- Weight: 1.5 lbs
- Warranty: 3 Years

