nFUSE® xl Lightbar

Dual-level lightbar with 360-degrees of continuous light



FEATURES

- Impressive addition to our full suite of products for fire and EMS apparatuses
- Built with a hardcoated lens to reduce scratching and surface deterioration
- Compatible with bluePRINT® control system that will connect the lightbar to all necessary sirens, speakers or perimeter lighting
- Arrow control modules can be combined with warning colors for maximum functionality
- Single or dual color capable on every module with independent upper and lower control
- Built-in ambient light sensor that can control when the bar is dimmed or at full intensity

SPECIFICATIONS

Input Voltage Range	10-32 Vdc
Amperage/Power	1A and 12.8W per module @ 12.8V
Standby Current/Power	*Ignition ON:* 0.025A per module @ 12.8V; 0.32W per module @ 12.8V *Ignition OFF:* <0.00025A total for any length bar
Operating Temperature	-40°C to +65°C / -40°F to +149°F
LED Options & Colors	Single or dual color (R) (B) (A) (G) (W)
Lens Options	(R) (B) (A) (G) (C) (T) *(options may vary and are selectable using the product configuration)*
Dimensions	*Lengths:* 24”, 36”, 42”, 48”, 54”, 60“ and 72” *Height:* 1.9" *Depth:* 12"
Mount Types	Standard fixed height mount, classic fixed height mount, extra low fixed height mount, XtraFit universal fixed height mount, headache rack mount
Certifications*	SAE J595 Class I Certified, SAE J845 Class I Certified, California Title 13 | ECE R10
Additional Compliance	Article 22 Compliant, NFPA 1900 Compliant, KKK-1822-F Compliant
Warranty	Five year

**When using compliant patterns. Certification may vary based on LED colors and flash patterns used*

Scan to order or learn more

Refer to soundoffsignal.com for standard part numbers and complete offerings.

CONTACT

Toll free 800-338-7337
Direct 616-896-7100
soundoffsignal.com

3900 Central Pkwy
Hudsonville, MI 49426
customerservice@soundoffsignal.com

V0724